

LDH42-PAI200

42" Wall-mounted Digital Signage



Features :

- Abundant interfaces including HDMI, DVI, DP, VGA, Audio in/out, USB, OPS slot
- 700 nits high brightness display, perfect image effect
- Metal housing design, anti-interference, high reliability and stable operation
- 178°H/178°V extra-wide viewing angle for overall viewing performance
- High fidelity digital processing, brilliant and vivid video



Technical Specification

Specification

| | |
|--------------------|----------------------|
| Model | LDH42-PAI200 |
| Panel Size | 42" TFT LCD |
| Display Ratio | 16:9 |
| Maximum Resolution | 1920×1080 |
| Display Color | 1.07B |
| Brightness (nits) | 700cd/m ² |
| Contrast | 1300:1 |
| Viewing Angle | 178°/178° |
| Response Time | 8ms |
| Backlight | LED |
| Network Mode | Wired |
| Internal Speaker | 10W×2 |

Signal Input

| | |
|----------|---|
| OPS Slot | 1 |
| RJ45 | 1 |
| HDMI | 2 |
| DVI | 1 |

| | |
|---------|---|
| DP | 1 |
| VGA | 1 |
| AV | 1 |
| USB 2.0 | 1 |
| Audio | 1 |
| IR | 1 |
| RS232 | 1 |

Signal Output

| | |
|---------|---|
| DVI | 1 |
| DP | 1 |
| Audio | 1 |
| IR | 1 |
| RS232 | 1 |
| Speaker | 1 |

Others

| | |
|--------------|---|
| Dimension | 947.0×541.0×71.1mm(Handle)/56.8mm(Wall Mount) |
| Package Size | 1123×203×743mm |

| | |
|----------------------|----------------------|
| Net Weight | 15.3kg |
| Body Material | Metal Plate |
| Installation Mode | Wall-mounted |
| VESA | 200x200 |
| Display Mode | Portrait, Landscape |
| Power | AC100-240V, 50/60Hz |
| Standard Consumption | 100W |
| Standby Consumption | ≤0.5W |
| Work Environment | Temperature: 0℃~+40℃ |
| | Humidity: 20%~80% |

Dimensions(mm)

