

LDV55-HAO200

55" Floor-standing Full Outdoor Digital Signage



Features :

- Industrial design, IP55 waterproof metal housing, tempered protective glass.
- 2500nits high brightness and anti-reflection glass is ensured excellent visibility under direct sunlight.
- Built-in temperature regulator, works well in extreme cold or hot weather.
- 178°H/178°V extra-wide viewing angle for overall viewing performance
- Supports picture, audio, video, text display and screen control remotely.



Technical Specification

Display

Model	LDV55-HAO200
Screen Size	55" TFT LCD
Aspect Ratio	9:16
Resolution	1080×1920
Display Colors	16.7M (8 bits)
Brightness	2500nits
Contrast Ratio	4000:1
Viewing Angle(H×V)	178°/178°
Display Mode	Portrait
Response Time	8ms
24/7 Operation	Yes

Connectivity

Input	SD, RJ45, USB2.0*2, HDMI
Output	N/A
External Control	RS232
Wifi	Yes
Speaker	5W×2
SMART Signage Platform	Media Publish System

Power & Environmental Conditions

Power Supply	AC100-240V (+/- 10%), 50/60Hz
Consumption(Typical)	480W(880W with heater)
Consumption(Standby)	Less than 0.5W
Operating Temperature	-40°C~+50°C(-40°F~122°F)
Operating Humidity	5%~95%
Protection Level	IP55

Dimensions(W×H×D) & Weight

With Pedestal	2000×850×160mm (78.7"×33.5"×6.3")
Packaging	2152×1005×515mm(84.7"×39.6"×20.3")
Net Weight	180kg (396.8lb)
Gross Weight	210kg(463.0lb)

Internal Player

Processor	Cortex-A7 1.5GHz Quad Core CPU
RAM	2GB
Storage	8GB
Multimedia	mp4, avi, mov, asf, wmv, rm, rmvb, mkv, jpg, jpeg, gif, bmp, png, mp3, wma, wav, pdf
Operating System	Android 5.1
Decoding Capacity	1ch@4K or 4ch@1080P