

LS490YXS-EF

49" FHD Video Wall Display Unit (Narrow Bezel 11.8mm)



Features:

- \cdot Industrial level wide viewing angle panel, suitable for extensive 24/7 continuous works
- ·11.8mm bezel-to-bezel design(5.9mm even panel bazel)
- \cdot Full high definition resolution, high image quality, and no light-leaking
- · Built-in 3D COMB filter and 3D Noise Reduction
- \cdot Built-in automatic ghost elimination function to protect the long-term use of LCD screen
- · Professional thermal design to extend equipment lifespan.
- · Abundant interfaces HDMI, DVI, VGA, BNC, support video loop
- · Infrared, software control, supporting remote PC control
- · Brightness smart detection, power-saving











Technical Specification

VI	od	e
----	----	---

Model	LS490YXS-EF
System	
Diagonal	49"(16:9)
Resolution	1920×1080 (FHD)
Bezel Width	5.9mm(U/L/R/B)
Backlight	LED
Brightness/Luminance (Standard)	380 cd/m ²
Contrast	1200:1
Angle of view	H178°, V178°
Response Time	8ms
Display Color	8bit(16.7M)
VESA	400×400mm

Video Signals

Input	VGA(D-Sub)×1, CVBS(BNC)×2, DVI-D×1, HDMI×1, RS232(RJ45)×1, USB×1	
Output	CVBS(BNC)×2, RS232(RJ45)×1	
	Speaker	10W×2

General

Consumption (Standard)	70W
Consumption (Standby)	≤1W
Power Supply	AC100~240V (±10%), 50/60Hz
Gross Weight	20.0kg
Net Weight	15.0kg
Dimensions (with frame)	1090.4×621.3×45.5mm
Installation Mode (all optional)	Wall-mounted, base installation
Control signal	Infrared, RS232 double mode, supporting remote PC control
Work Environment	Temperature: 0 °C ~50 °C
	Humidity: 20%~90%

Accessory

Standard	VGA cable, power cable, remote control
Optional	Pedestal, hanging bracket



Dimensions(mm)





