

PHOA16-SS

Outdoor Fixed LED



Features:

- Adopt special material and devices, to achieve anti-static, anti-interference and anti-corrosion function.
- Display with no granular, good uniformity, and no mosaic phenomenon.
- Precision finishing cabinet, seamless splicing.
- Aging test under high and low temperature.



Technical Specification

Model

Model	PHOA16-SS
-------	-----------

Parameters

Pixel Pitch	16mm
Module Size (W×H)	256×256mm
Module Resolution (W×H)	16×16
Pixel Type	1R1G1B
LED Type	DIP346
Cabinet Size (W×H×D)	1024×1024×120mm
Cabinet Resolution (W×H)	64×64
Cabinet Material	Iron
Cabinet Weight	55 kg/cabinet
Pixel Density	3,906 dots/m ²
Brightness	7500 cd/m ²
Grey Level	14 bits
Color	4.4 trillion
Contrast	1000:1

Refresh Rate	2880 Hz
Driving Mode	1/4 scan
Viewing Angle	120°/60°
Ingress Protection (front/rear)	IP65/IP54
Input Voltage	AC100~240V (+/-10%), 50/60 Hz
Work Temperature	-20 °C ~+50 °C
Work Humidity	10%RH~90%RH
Input Power (max)	650 W/m ²
Input Power (avg)	260 W/m ²
Communication Connection	CAT5 Cable (L≤100m); single mode fiber (L≤10km)
Maintenance Mode	Rear Maintenance