

LM55-S401

55" UHD LED Monitor



Features:

- 4K Ultra-HD resolution
- Industrial level LCD panel, suitable for continuous 24/7 operation
- Slim 5.2mm ultra-narrow bezel design
- Built-in 3D COMB filter and 3D noise reduction
- 7ms fast response time for no motion blur, judder or ghosting
- 1.07B colors, for a realistic and immersive visual experience
- High fidelity digital processing for a brilliant and vivid video
- 178°/178° wide uninterupted viewing angle
- Using tamper-proof metal housing
- Professional thermal design to extend equipment lifespan
- Built-in power, low energy consumption, ultra-quiet
- Wide array of connectivity options HDMI, DVI, VGA, BNC, USB multimedia

Technical Specification

Model

Model	LM55-S401
-------	-----------

Display


Screen Size	55"
Aspect Ratio	16:9
Resolution	3840×2160 (UHD)
Backlight	LED
Brightness/Luminance	500 cd/ m ²
Contrast	4000:1
Display Color	1.07B(10bit)
Viewing Angle(H/V)	178°(H)/178°(V)
Response time	7ms
Refresh Rate	60Hz

Signals

Input	VGA(D-Sub)×1, CVBS(BNC)×1, DVI-D×1, HDMI×2, RS232×1, USB 2.0×1	
	Audio×1, RS232×1	
Output	Speaker	
		10W×2

General

Power Supply	AC100~240V (+/-10%), 50/60 Hz
--------------	-------------------------------



Consumption (Standard)	160W	
Consumption (Standby)	≤0.5W	
Type	Internal	
Net Weight	20kg (44.1lb)	
Gross Weight	30kg (66.1lb)	
Bezel Width	5.2mm (U/L/R/B)	
Wall Mount	400×400mm (15.7"×15.7")	
Dimension without standard (W×H×D)	1222.0×692.8×63.2mm (48.1"×27.3"×2.5")	
Package(W×H×D)	1365×857×205mm (53.7"×33.7"×8.1")	
Work Environment	Temperature	0°C~50°C (32°F~122°F)
	Humidity	20%~90%

Accessory

Standard	VGA cable, power cable, remote control
Optional	Pedestal, hanging bracket

Certifications

Certifications	CE/FCC
----------------	--------

Dimensions(mm)

